



MASTER xp5000 5W/40

API SM/CF ACEA A3/B4

Doill Automobile - Vehicle Oil

Motor Oil

Fully Synthetic

Usage

Doill MASTER xp5000 5W/40 range of lubricants are ultra premium synthetic engine oils, designed to provide outstanding levels of protection and performance. **Doill MASTER xp5000 5W/40** products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend **Doill MASTER xp5000 5W/40** if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress. It is suitable for gasoline, diesel and LPG cars.

Performance

Doill MASTER xp5000 5W/40 fully synthetic motor oil, the performances it provides in your vehicle:

- It has a high TBN value.
- It helps to prevent soot effectively.
- Shows good engine cleaning performance.
- Provides strong protection against abrasion.
- Prevents high temperature viscosity loss.
- Can be used on relatively old engine technologies.
- Compatible for Gasoline, Diesel and LPG.
- It is used in passenger cars, SUVs (sports utility vehicles), light commercial vehicles and pickup trucks.
- It is an ideal engine oil for highway driving and stop-and-go city driving.

Recommendation

- **Doill MASTER xp5000 5W/40** can only be mixed with similar products
- Replace the product with professional support
- Before using the product, refer to the vehicle user manual.
- You can contact Doill for detailed information on product usage.

Meets or exceeds the following performance levels:	
ACEA	A5/B5
API	SM
MB	229.3
BMW	Longlife-01
VW	500.00 / 502.00 / 505.00
PEUGEOT/CITROEN	B71 2296
RENAULT	RN0710 / RN0700
FIAT	Meets Fiat 9.55535-S2, Dexos2*



Features and Specifications

Viscosity Grade, SAE	5W/40
Kinematic Viscosity @ 100 °C, mm ² /s, ASTM D445	14.1
Kinematic Viscosity @ 40 °C, mm ² /s, ASTM D445	91
Viscosity Index, ASTM D2270	165
Pour Point, °C, ASTM D97	-39
Flash Point, °C, ASTM D92	225
Density @ 15 °C, g/cm ³ , ASTM D4052	0,860

Doill MASTER xp5000 5W/40
07 December 2021

Doill, the Doill logo and related marks are trademarks of Doğan Boya Makine Ve Kimya Sanayi Limited Şirketi, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information you can call +90 850 302 41 40

Lubricant Is Our Business

Contact Us: +90 850 302 41 40

www.doill.com.tr

e-mail: info@doill.com.tr