



TESLA RTX 2000 15W/40

API SL/CF ACEA A3/B4

Doill Light Commercial Vehicle

Motor Oil

Usage

Doill TESLA RTX 2000 15W/40 is an excellent performance multigrade engine oil specially designed and formulated to provide extra high level of engine protection and superior performance for engines running under the most severe conditions. It is exclusively formulated with premium quality unconventional base oils and advanced additives system to provide outstanding thermal and oxidation stability that ensures minimum oil thickening at very high operating temperature, excellent deposits control and minimized engine wear and tear.

Performance

Doill TESLA RTX 2000 15W/40 engine oil performs in your vehicle:

- Provides superior protection against engine sludge
- Advanced protection against viscosity and thermal breakdown.
- Premium quality base oils and anti wear additives to help extend the life of your engine.
- Helps minimize oil consumption
- Protects for up to 4000 miles between oil changes.

Area Of Usage

Doill TESLA RTX 2000 15W/40 A3/B4 is suitable for use in automotive and light commercial vehicle gasoline, diesel and LPG engines where the manufacturer recommends an ACEA A3/B3, SL/CF and earlier specification 15W/40 lubricant.

Suggestions

- **Doill TESLA RTX 2000 15W/40** can only be mixed with similar products
- Replace the product with professional support
- Before using the product, refer to the vehicle user manual.
- You can contact Doill for detailed information on product usage.



Features and Specifications

Viscosity Grade, SAE	15W/40
Kinematic Viscosity @ 100 °C, mm ² /s, ASTM D445	14.9
Kinematic Viscosity @ 40 °C, mm ² /s, ASTM D445	109
Viscosity Index, ASTM D2270	142
Pour Point, °C, ASTM D97	-36
Flash point, Cleveland Open Cup, °C, ASTM D92	224
Total Base Number, mgKOH/g, ASTM D2896	7.2
Density @ 15 °C, g/cm ³ , ASTM D4052	0.865

Doill TESLA RTX 2000 15W/40
12 February 2018

Doill, the Doill logo and related marks are trademarks of Doğan Boya Makine Ve Kimya Sanayi Limited Şirketi, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information you can call +90 850 302 41 40

Lubricant Is Our Business

Contact Us: +90 850 302 41 40

www.doill.com.tr

e-mail: info@doill.com.tr