



TESLA RTX 5400 5W/40

API SL/CF ACEA A3/B4

Automobile

Motor Oil

Usage

Doill TESLA RTX 5400 5W/40

- Specially designed for new generation engines using LGP.
- Recommended for all gasoline passenger and commercial vehicles.
- It can be used in diesel powered passenger and commercial vehicles.

It is recommended to use the **doill MASTER xp5400** series for a better experience.

Performance

Doill TESLA RTX 5400 5W/40 engine oil performs in your vehicle:

- Provides superior protection against engine sludge
- Advanced protection against viscosity and thermal breakdown.
- Premium quality base oils and anti wear additives to help extend the life of your engine.
- Helps minimize oil consumption
- Protects for up to 5000 miles between oil changes.

Area Of Usage

Doill TESLA RTX 5400 5W/40 A3/B4 is suitable for use in automotive and light commercial vehicle gasoline, diesel and LPG engines where the manufacturer recommends an ACEA A3/B3, SL/CF and earlier specification 10W/40 lubricant.

Suggestions

- **Doill TESLA RTX 5400 5W/40** can only be mixed with similar products
- Replace the product with professional support
- Before using the product, refer to the vehicle user manual.
- You can contact Doill for detailed information on product usage.



TESLA
RTX 5400
5W/40
TAXI GAS

TESLA SERIES



Features and Specifications

Viscosity Grade, SAE	5W/40
Kinematic Viscosity @ 100 °C, mm ² /s, ASTM D445	14.5
Kinematic Viscosity @ 40 °C, mm ² /s, ASTM D445	95
Viscosity Index, ASTM D2270	158
Pour Point, °C, ASTM D97	-39
Flash point, Cleveland Open Cup, °C, ASTM D92	224
Density @ 15 °C, g/cm ³ , ASTM D4052	0.865

Doill TESLA RTX 5400 5W/40
12 February 2018

Doill, the Doill logo and related marks are trademarks of Doğan Boya Makine Ve Kimya Sanayi Limited Şirketi, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information you can call +90 850 302 41 40

Lubricant Is Our Business

Contact Us: +90 850 302 41 40

www.doill.com.tr

e-mail: info@doill.com.tr

doill

Doğan Boya Makine ve Kimya Sanayi LTD. ŞTİ.
All Rights Are Reserved.