



Doill > Doill SPEED RACER RS100 10W/60 TDS > English

SPEED RACER RS100 10W/60

API SN/CF ACEA A3/B4
Doill Automobile - Vehicle Oil

Motor Oil

Fully-Synthetic

Usage

Doill SPEED RACER RS100 10W/60 fully synthetic, Titanium-Gold Alloy Technology lubricant, specially designed for high performance cars with naturally aspirated, compressed or turbocharged engines. Recommended for Aston Martin / Alfa Romeo GT séries / Lotus / BMW M Séries / Mercedes / Maserati / Ferrari V12 / TVR / Lancia / Jaguar / Audi R8 5.2L GT etc. Suitable for all kind of operating conditions and for all type of fuels : leaded or unleaded Gasoline, ethanol, LPG and Diesel. Compatible for catalytic converters.

Performance

Doill SPEED RACER 10W/60 fully synthetic motor oil, the performances it provides in your vehicle:

- Due to the use according to Formula 1 standards, it is used in high-level vehicles and modified engines, small, unexamined, undesigned at high revs.
- Compressors provide compressors in front of them.
- Makes a superior film in management through Titanium Gold Technology.
- Thanks to its high viscosity, it fills the organizations in the engine and consists of information from the source.
- It reduces oil burning in the engine.
- The oil smoke coming out of the exhaust minimizes the system.
- It provides full lubrication at the first start, under the safest conditions, with its full structure.
- Thanks to its high TBN value, it makes your engine ultra clean.
- Takes care of worn out engines.
- Protects for up to 9.000 miles between oil changes

Recommendation

- **Doill SPEED RACER RS100 10W/60** can only be mixed with similar products
- Replace the product with professional support
- Before using the product, refer to the vehicle user manual.
- You can contact Doill for detailed information on product usage.

Meets or exceeds the following performance levels:	
ACEA	A3/B4
API	SN
BMW	BMW M-MODELS
MERCEDES	MB 229.31
FIAT	9.55535-H3
ALFA ROMEO	GT Series
AUDI	R8 5.2L GT (CMPA)
VOLKSWAGEN	VW 501 01 / 505 00
• ASTON MARTIN	• MASERATI
• FERRARI V12	• JAGUAR
• LANCIA	• LOTUS
• TVR	



Titanium Gold Alloy Tech
FULLY-SYNTHETIC

SPEED RACER SERIES

SPEED RACER RS100 10W/60

Doill SPEED RACER RS100 10W/60 is a fully synthetic, performance oil produced for vehicles where high performance is required. It is the most performance engine oil produced by doill engine oils that provide high viscosity at high temperatures, low viscosity at low temperatures, designed according to formula 1 standards, providing the high viscosity needed by the engines used in cycles in motor sport vehicles, and at the same time making ultra lubrication.

Together with its fully synthetic structure and superior lubricating additive technology, it provides superior performance in new generation vehicles. It is recommended for performance engines where high viscosity is required. In addition, it reduces engine noise and oil burning by filling the gaps needed by the engine in worn out engines.

USAGE RECOMMENDATIONS

- Recommended for new generation gasoline vehicles and all vehicles with old model, Diesel, Gasoline and LPG.
- It is designed for modified vehicles used for motor sport.
- It is suitable for use in all old vehicles. (including LPG vehicles)
- Recommended for vehicles that burn oil, have a noisy engine and emit smoke. (It is not recommended for motor vehicles used in new generation engines and recommended for vehicles with particulate filters, with 0W/20, 0W/30, 0W/40 viscosity classes and with thin channels.
- It is recommended to wait a minimum of 45 seconds when you start your vehicle for the first time.



SPEED RACER RS200 5W/50

Doill SPEED RACER RS200 5W/50 is the most performance engine oil produced by doill engine oils, designed according to Formula 1 standards, providing the high viscosity required by the engines used in revving in motor sport vehicles and at the same time providing ultra lubrication, superior cleaning in engines thanks to its high TBN value. . Together with its fully synthetic structure and superior lubricant additive technology with doill's Titanium-Gold Alloy Technology, it provides superior performance in new generation vehicles. It is recommended for performance engines where high viscosity is required. In addition, it reduces engine noise and oil burning by filling the gaps needed by the engine in worn out engines.



USAGE RECOMMENDATIONS

- Suitable for new generation, high horsepower diesel and gasoline vehicles. (You can use it new generation engines and recommended for vehicles with particulate filters.)
- It is designed for modified vehicles used for motor sport.
- It is suitable for use in all old vehicles. (including LPG)
- Recommended for vehicles that burn oil, have a noisy engine and emit smoke. (We recommend **Doill SPEED RACER RS100 10W/60** for better treatment on older vehicles.)
- It is recommended to wait a minimum of 45 seconds when you start your vehicle for the first time.

Doill SPEED RACER RS100 10W/60 Features and Specifica-

Features and Specifications

Viscosity Grade, SAE	10W/60
Kinematic Viscosity @ 100 °C, mm ² /s, ASTM D445	24
Kinematic Viscosity @ 40 °C, mm ² /s, ASTM D445	163,7
Viscosity Index, ASTM D2270	178
Pour Point, °C,ASTM D97	-39
Sulfated ash, Weight %, ASTM D874	1.16
Poshphorus, Weight %, ASTM D4951	0.125
HTHS Viscosity @ 150 C 1x10(6) sec(-1), Sheared, mPa.s, ASTM D4683	5.9
Total Base Number, mgKOH/g, ASTM D2896	9,4
Density @ 15 °C, g/cm ³ , ASTM D4052	0.870


**SPEED
RACER**

**RS100
10W/60**

Titanium Gold Alloy Tech
FULLY-SYNTHETIC



**Engine
Performance**



Oil Consumption



Lubrification



**Compressor
Efficiency**

Doill SPEED RACER RS100 10W/60
17 April 2019

Doill, the Doill logo and related marks are trademarks of Doğan Boya Makine Ve Kimya Sanayi Limited Şirketi, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information you can call +90 850 302 41 40

Lubricants Are Our Business

Contact Us: +90 850 302 41 40

www.doill.com.tr

e-mail: info@doill.com.tr

doill

Doğan Boya Makine ve Kimya Sanayi LTD. ŞTİ.
All Rights Are Reserved.