

Doill MEGATRON EV W1 CHANGAN CA DHTF-1

Fluid for transmissions with wet e-Motors

ELECTRICAL VEHICLE AUTOMATIC TRANSMISSION FLUID

Transfer Case and Power Steering

Fully Synthetic

Usage

Doill MEGATRON EV W1 CHANGAN CA DHTF-1 is a new-generation EV transmission fluid developed specifically for wet e-motor transmissions, formulated with fully synthetic Poly Alpha Olefin (PAO) base oils to deliver high performance and high efficiency. It helps extend the service life of drivetrain systems while enabling vehicles to travel longer distances on a single charge. Thanks to its excellent electrical properties, electrical conductivity shows minimal change even in used fluid, ensuring consistent performance throughout the fluid's service life. This advanced formulation supports increasing torque demands and maximum efficiency, offers superior oxidative stability for extended service intervals, and provides effective cooling performance due to its high heat capacity and thermal conductivity. The product is specially manufactured to meet the **CHANGAN CA DHTF-1** specification.

Performance

Doill MEGATRON EV W1 CHANGAN CA DHTF-1 the advantages of synthetic oil in automatic transmission transitions:

- Complete coverage: wet e-motors
- Ultra Protection For e-Transmission
- Excellent Electrical Properties
- Superior Oxidative Stability
- Outstanding di-electrical properties:
 1. low conductivity
 2. high resistance
 3. high breakdown voltage
- Perfect balance between reduced fluid viscosity and extremely good gear and bearing protection.
- Very good cold flow properties.
- Outstanding pumpability at low operating temperatures.
- Provides exceptional copper corrosion protection for better hardware durability
- Provides long-lasting oil usage and prevents oil deterioration at high operating temperatures.
- Provides excellent oxidation and thermal stability to provide longer fluid life.
- It is fully synthetic.
- Excellent gear protection.
- It has been tested against all seasonal conditions.
- PAO (Poly Alpha Olefin) based

Suggestions

Doill MEGATRON EV W1 CHANGAN CA DHTF-1, an only be mixed with liquids of similar properties Replace the product with professional assistance. Before using the product, refer to the vehicle owner's manual. You can contact Doill for detailed information about the use of the product.



Application

Meets or exceeds the following performance levels:

- Changan (All Models)
- Xiaomi SU7
- Avatr 06
- Avatr 07
- Avatr 11
- Avatr 12



1 L | T244694017
2.5 L | T244694024
208 L | T244694041

Features and Specifications

Density @ 15 °C, g/cm ³ , ASTM D4052	0.83
Kinematic Viscosity @ 100 °C, mm ² /s, ASTM D445	5.25
Kinematic Viscosity @ 40 °C, mm ² /s, ASTM D445	24.05
Viscosity Index, ASTM D2270	160
Brookfield - 40 °C (cP), DIN 51398	5875
Colour, Appearance	Yellow
Pour Point, °C, ISO 3016	-48
Flash Point, °C, ASTM D92	205

Doill MEGATRON EV W1 CHANGAN CA DHTF-1
28 July 2024

Doill, the Doill logo and related marks are trademarks of Doğan Boya Makine Ve Kimya Sanayi Limited Şirketi, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information you can call +90 850 302 41 40

Lubricants Are Our Business

Contact Us: +90 850 302 41 40

www.doill.com.tr

e-mail: info@doill.com.tr